

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

SEMICONDUCTOR DEVICE AND PRODUCTION THEREOF

Patent Number: JP8064634
 Publication date: 1996-03-08
 Inventor(s): YAMADA TOMIO.; MURAKAMI HAJIME
 Applicant(s): HITACHI LTD
 Requested Patent: ☐ JP8064634
 Application Number: JP19940221113 19940823
 Priority Number(s):
 IPC Classification: H01L21/60; H01L29/78
 EC Classification:
 Equivalents: JP3027512B2

Abstract

PURPOSE: To enhance the performance of a product by connecting each inner lead directly with a pellet at each connecting part thereby decreasing the external resistance significantly as compared with an electrical connection through bonding wire and separating a header from an inner lead group so that a best material can be employed for the inner lead and the header.

CONSTITUTION: A power transistor comprises a planar pellet 10 on which an MOSFET circuit is fabricated, three inner leads 35, 36, 37, a header 41 for enhancing the heat dissipation performance, and a resin seal 44 sealing the pellet 10, the inner lead group and a part of the header. Each inner lead is connected electrically and mechanically with a connecting part 25, 26, i.e., a bump, on the circuit side major surface of the pellet 10 and the header 41 is jointed to the opposite major surface of the pellet.

Data supplied from the esp@cenet database - 12